

# Cable M12 to pigtail, 2 m

**P/N: T911852ACC**

**Copyright**

© 2023, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

**Document identity**

Publ. No.: T911852ACC  
 Commit: 64986  
 Language: en-US  
 Modified: 2020-03-31  
 Formatted: 2023-03-31

**Website**

<http://www.flir.com>

**Customer support**

<http://support.flir.com>

**Disclaimer**

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to [exportquestions@flir.com](mailto:exportquestions@flir.com) with any questions.



General description	
Cable to access signals in M12 connector, pigtail.	
Physical data	
Weight	0.120 kg (0.26 lb)
Cable length	2 m (6.6 ft)
Connector	M12 to pigtail
Color	Black
Shipping information	
Packaging, type	Cardboard box
Packaging, weight	0.190 kg (0.42 lb)
Packaging, size	157 × 130 × 65 mm (6.18 × 5.12 × 2.56 in)
EAN-13	7332558025925
UPC-12	845188021764

**Compatible with the following products:**

- 89829-0201; FLIR A50 29° Research & Development Kit
- 89851-0201; FLIR A50 51° Research & Development Kit
- 89895-0201; FLIR A50 95° Research & Development Kit
- 89829-0101; FLIR A50 Thermal Core 29°
- 89851-0101; FLIR A50 Thermal Core 51°
- 89895-0101; FLIR A50 Thermal Core 95°
- 89929-0201; FLIR A70 29° Research & Development Kit
- 89951-0201; FLIR A70 51° Research & Development Kit
- 89995-0201; FLIR A70 95° Research & Development Kit
- 89929-0101; FLIR A70 Thermal Core 29°
- 89951-0101; FLIR A70 Thermal Core 51°
- 89995-0101; FLIR A70 Thermal Core 95°
- 89829-1101; FLIR A50 Thermal Core 29°, Optional temperature range
- 89851-1101; FLIR A50 Thermal Core 51°, Optional temperature range
- 89895-1101; FLIR A50 Thermal Core 95°, Optional temperature range
- 89929-1101; FLIR A70 Thermal Core 29°, Optional temperature range
- 89951-1101; FLIR A70 Thermal Core 51°, Optional temperature range
- 89995-1101; FLIR A70 Thermal Core 95°, Optional temperature range
- 85900-0000; FLIR A700 Thermal Core
- 85900-1100; FLIR A700 Thermal Core, Optional temperature range
- 85902-0102; FLIR A700 24° Professional Science Kit
- 85902-0202; FLIR A700 24° Standard Science Kit
- 85903-0102; FLIR A700 24° f/1.0 Professional Science Kit
- 85903-0202; FLIR A700 24° f/1.0 Standard Science Kit
- 90600-0000; FLIR A500 Thermal Core
- 90600-1100; FLIR A500 Thermal Core, Optional temperature range



## Cable M12 to pigtail, 2 m

---

**P/N: T911852ACC**

© 2023, FLIR Systems, Inc.

#T911852ACC; r. 64986; en-US

- 90610-0202; FLIR A500 24° Standard Science Kit
- 90611-0102; FLIR A500 24° Professional Science Kit
- 91900-0000; FLIR A400 Thermal Core
- 91900-1100; FLIR A400 Thermal Core, Optional temperature range
- 91902-0202; FLIR A400 24° Standard Science Kit
- 91903-0102; FLIR A400 24° Professional Science Kit
- 86401-0101; FLIR GF77a 25° LR
- 86403-0101; FLIR GF77a 6° LR