

P/N: T911183

Copyright

© 2023, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: T911183

Commit: 64137

Language: en-US

Modified: 2020-02-26

Formatted: 2023-03-31

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



| | |
|---|--|
| General description | |
| Power supply, power over Ethernet (PoE) injector incl. multi plugs. | |
| Power system | |
| AC operation | Input: 100–240 V, 50–60 Hz |
| DC operation | Output: 56 VDC |
| Power | 15.4 W |
| Physical data | |
| Size (L x W x H) | 86x 50 x 33 mm (3.4 x 2.0 x 1.3 in.) |
| Color | Black |
| Shipping information | |
| List of contents | <ul style="list-style-type: none"> PoE injector EU plug UK plug US plug AU plug |
| EAN-13 | 7332558008683 4743254001787 (Estonia plant) |
| UPC-12 | 845188009205 |
| Country of origin | China |

Compatible with the following products:

- 89829-0201; FLIR A50 29° Research & Development Kit
- 89851-0201; FLIR A50 51° Research & Development Kit
- 89895-0201; FLIR A50 95° Research & Development Kit
- 89829-0101; FLIR A50 Thermal Core 29°
- 89851-0101; FLIR A50 Thermal Core 51°
- 89895-0101; FLIR A50 Thermal Core 95°
- 89929-0201; FLIR A70 29° Research & Development Kit
- 89951-0201; FLIR A70 51° Research & Development Kit
- 89995-0201; FLIR A70 95° Research & Development Kit
- 89929-0101; FLIR A70 Thermal Core 29°
- 89951-0101; FLIR A70 Thermal Core 51°
- 89995-0101; FLIR A70 Thermal Core 95°
- 89829-1101; FLIR A50 Thermal Core 29°, Optional temperature range
- 89851-1101; FLIR A50 Thermal Core 51°, Optional temperature range
- 89895-1101; FLIR A50 Thermal Core 95°, Optional temperature range
- 89929-1101; FLIR A70 Thermal Core 29°, Optional temperature range
- 89951-1101; FLIR A70 Thermal Core 51°, Optional temperature range

P/N: T911183

© 2023, FLIR Systems, Inc.

#T911183; r. 64137; en-US

- 89995-1101; FLIR A70 Thermal Core 95°, Optional temperature range
- 85900-0000; FLIR A700 Thermal Core
- 85900-1100; FLIR A700 Thermal Core, Optional temperature range
- 85902-0102; FLIR A700 24° Professional Science Kit
- 85902-0202; FLIR A700 24° Standard Science Kit
- 85903-0102; FLIR A700 24° f/1.0 Professional Science Kit
- 85903-0202; FLIR A700 24° f/1.0 Standard Science Kit
- 90600-0000; FLIR A500 Thermal Core
- 90600-1100; FLIR A500 Thermal Core, Optional temperature range
- 90610-0202; FLIR A500 24° Standard Science Kit
- 90611-0102; FLIR A500 24° Professional Science Kit
- 91900-0000; FLIR A400 Thermal Core
- 91900-1100; FLIR A400 Thermal Core, Optional temperature range
- 91902-0202; FLIR A400 24° Standard Science Kit
- 91903-0102; FLIR A400 24° Professional Science Kit
- 83225-0101; FLIR A35 FOV 13 (60 Hz, ver. 2017)
- 83213-0102; FLIR A35 FOV 25 (60 Hz, ver. 2017)
- 83207-0102; FLIR A35 FOV 45 (60 Hz, ver. 2017)
- 83209-0102; FLIR A35 FOV 69 (30 Hz, ver. 2017)
- 73413-0102; FLIR A65 f=13 mm with SC kit (30 Hz)
- 73513-0102; FLIR A65 f=13 mm with SC kit (7.5 Hz)
- 75025-0101; FLIR A65 FOV 25 (30 Hz, ver. 2016)
- 75013-0101; FLIR A65 FOV 45 (30 Hz, ver. 2016)
- 75007-0101; FLIR A65 FOV 90 (30 Hz, ver. 2016)
- 86401-0101; FLIR GF77a 25° LR
- 86403-0101; FLIR GF77a 6° LR